



## Intonachino Classico '700'

**Origin:** Bericalce Italy

**Texture:** Dolomite lime with 12 months of ageing, limestone derivatives, selected Carrara marble granules, granulometry 0.5~0.8 mm. (VOC: 0 / Ecological material )

**Applications:** Walls: Indoor / Outdoor spaces (In Plasterboard infrastructures, Smooth plaster, Marble, Tiles, Concrete, MDF). Suggested for external Heat Insulation.

**Properties:** Due to its ecological texture and its hydraulic lime content it becomes active by humidity (It absorbs humidity in a wet environment and discards it in a dry environment). At the same time it allows the free perspiration of walls thus regulating the "microclimate" of indoor spaces. Due to the absence of concrete it does not develop Alkalizations (white blotches)

**Technical characteristics:** Tensile strength 10N/mm<sup>2</sup> – Compression strength: 40 N/mm<sup>2</sup> – Steam permeability SD ~0.04m (DIN 52615) – Water absorption: W=0.3kg/cm<sup>2</sup> : 1/2h PH13

**Texture:** Slightly granular with a few color variations due to the natural ageing process of the lime.

**Suggested consumption:** 1.1kg/layer (Applied in 2 layers)

**Total thickness:** 2.2 mm

**Package:** Ready-made paste in a 25 kg bucket (duration of workability of a bucket after opening: 3 months)

**Colorings:** 30 standard colors and all NCS-RAL colors on demand