



## Marmorino Pasta Media

**Origin:** Impex Italy

**Texture:** Lime and limestone derivatives. Lime with 16 months of ageing, Marbles of controlled cutting, granulometry 0.3~0.5 mm. (VOC: 0 / Ecological material)

**Applications:** Walls / Floorings: Indoor / Outdoor spaces (In Plasterboard infrastructures, Smooth plaster, Marble, Tiles, Concrete, MDF, Floor heating).

**Application:** With a stainless spatula

**Properties:** Due to its ecological texture and its hydraulic lime content it becomes active by humidity (It absorbs humidity in a wet environment and discards it in a dry environment). At the same time it allows the free perspiration of walls thus regulating the "microclimate" of indoor spaces. Due to the absence of concrete it does not develop Alkalizations (white blotches). For applications on floorings complete waterproofing is proposed by using 2 ingredient crystallization, with a polyurethane -based semi-impregnation, with a MAT – SATINY result.

**Technical characteristics:** Tensile strength 10N/mm<sup>2</sup> – Compression strength 46N/mm<sup>2</sup> – Steam permeability SD~0.03m (DIN 52615) – Water absorption: W=0.2kg/cm<sup>2</sup>:1/2h PH13

**Proposed consumption:** 1.1kg/layer (Applied in 2 layers)

**Total thickness:** 2.2 mm

**Package:** Readymade paste in a 25 kg bucket (duration of workability of a bucket after opening: 3 months)

**Colorings:** 50 standard colors and all NCS-RAL colors on demand

**Tips:** For applications on floorings 6 day ageing is proposed before applying the crystallization..

**Texture – Appearance:** Very smooth– closed surface with the slightest color variations and natural marble appearance